

Kompac®

KOMPAC FOUNTAIN CONTROL SYSTEM

REFRIGERATED AND NON-REFRIGERATED RECIRCULATORS

8 GALLON NON-REFRIGERATED

FEATURES CONTINUOUS CIRCULATION AND FILTRATION WHILE INSURING A CONSTANT SUPPLY OF FRESH FOUNTAIN SOLUTION RESULTING IN LESS CONTAMINATION AND HIGHER QUALITY. THE STAINLESS STEEL CONSTRUCTION AND HIGH PERFORMANCE, CORROSION RESISTANT PUMP ALLOWS FOR LONG LIFE AND YEARS OF MAINTENANCE FREE OPERATION. THIS LOW PROFILE & AFFORDABLE CIRCULATOR IS THE PERFECT FIT FOR YOUR SINGLE AND 2/COLOR PRESSES.

8 AND 16 GALLON REFRIGERATED

FEATURES ONE (8 GALLON) OR TWO (16 GALLON) CORROSION RESISTANT PUMPS FEATURING AN AC MOTOR FOR LONG LIFE AND QUIET OPERATION. THE STAINLESS STEEL CONSTRUCTION MAINTAINS THE HIGHEST LEVEL OF QUALITY AND A CLEAN APPEARANCE.

THE CONTROL PANEL FEATURES:

- ONE TOUCH DIGITAL TEMPERATURE CONTROL
- EASY TO READ LED DISPLAY
- INDIVIDUAL PUMP AND CHILLER CONTROL

THESE 8 AND 16 GALLON REFRIGERATED RECIRCULATORS ARE A PERFECT FIT FOR 1-2 PRINT UNITS WHERE A MINIMUM FLUID TEMPERATURE OF 55° IS DESIRED.



ELECTRICAL SPECIFICATIONS

8 GALLON NON-REFRIGERATED

115 VOLTS, SINGLE PHASE, 60 Hz, 3 AMPS (US)
230 VOLTS, SINGLE PHASE, 50 Hz, 2 AMPS (EUROPE)

8 GALLON REFRIGERATED

115 VOLTS, SINGLE PHASE, 60 Hz, 3 AMPS (US)
230 VOLTS, SINGLE PHASE, 50 Hz, 2 AMPS (EUROPE)

16 GALLON REFRIGERATED

115 VOLTS, SINGLE PHASE, 60 Hz, 17 AMPS (US)
230 VOLTS, SINGLE PHASE, 50 Hz, 10 AMPS (EUROPE)

Kompac Technologies, LLC
7 Commerce Street
Somerville, NJ 08876
Tel: +1 908 534 8411
Fax: +1 908 534 8412
info@kompactech.com
sales@kompactech.com
www.kompactech.com

*Your Partner In Profit
for 30 Years!*

